

1. (amended) A method of verifying proper coupling of an implement assembly to a lift arm assembly by an operator who is located in a cab of a work machine, with (i) the work machine including the implement assembly and the lift arm assembly, (ii) the implement assembly including a hinge plate, (iii) the hinge plate having a first coupling aperture extending therethrough, (iv) the lift arm assembly having a lift arm and a cylinder, and (v) the cylinder being secured to the lift arm, comprising the steps of:

[actuating the cylinder] advancing a hydraulic fluid into a cylinder so as to move a pin from a first pin position to a second pin position, wherein (i) the pin is spaced apart from the first coupling aperture when the pin is located in the first pin position, and (ii) the pin extends through the first coupling aperture when the pin is located in the second pin position; and

viewing the pin when the pin is located in the second pin position by the operator from a position within the cab whereby proper coupling of the implement assembly to the lift arm assembly is verified by the operator without having to exit the cab.

7. (amended) A method of verifying proper coupling of an implement assembly to a lift arm assembly by an operator who is located in a cab of a work machine, with (i) the work machine including the implement assembly and the lift arm assembly, and (ii) the implement assembly having a first coupling aperture, comprising the steps of:

[actuating a cylinder] advancing a hydraulic fluid into a cylinder so as to move a pin from a first pin position to a second pin position, wherein (i) the pin is spaced apart from the first coupling aperture when the pin is located in the first pin position, and (ii) the pin is positioned within the first coupling aperture when the pin is located in the second pin position; and

viewing the pin when the pin is located in the second pin position by the operator from a position within the cab whereby proper coupling of the implement assembly to the lift arm assembly is verified by the operator without having to exit the cab.

15. A work machine, comprising:
a cab in which an operator may be located;
an implement assembly having an implement and a hinge plate secured thereto, wherein said hinge plate has a first coupling aperture extending therethrough; and
a lift arm assembly having a lift arm and a cylinder secured thereto, wherein (i) said cylinder is operable to move a pin between a first pin position and a second pin position in response to advancement of a hydraulic fluid within said cylinder, (ii) said pin is spaced apart from said coupling aperture when said pin is located in said first pin position, (iii) said pin extends through said coupling aperture when said pin is located in said second pin position, (iv) said pin is positioned within a field of vision of said operator when (A) said pin is located in said second pin position, and (B) said operator is located within said cab.